



K22

Engine ref.	KD11903M
Alternator ref.	ECP 28 M/4
Performance class	G2

DESCRIPTIVE

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	NEXYS
Optional control panel	TELYS

POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
220 TRI	17.2	21.5	15.6	19.5	56
415/240	17.2	21.5	15.6	19.5	30
400/230	17.2	21.5	15.6	19.5	31
380/220	17.2	21.5	15.6	19.5	33
200/115	17.2	21.5	15.6	19.5	62
240 TRI	17.2	21.5	15.6	19.5	52
230 TRI	17.2	21.5	15.6	19.5	54

DIMENSIONS COMPACT VERSION

Length (mm)	1410
Width (mm)	720
Height (mm)	1080
Dry weight (kg)	490
Tank capacity (L)	50

DIMENSIONS SOUNDPROOFED VERSION

Commercial reference of the enclosure	M126
Length (mm).	1750
Width (mm).	775
Height (mm).	1230
Dry weight (kg).	660
Tank capacity (L).	50
Acoustic pressure level @1m in dB(A)	71
Sound power level guaranteed (Lwa)	87



K22

ENGINE CHARACTERISTICS

GENERAL ENGINE DATA

Engine model	KOHLER
Engine ref.	KDI1903M
Air inlet	Athmo
Cylinders arrangement	L
Number of cylinders	3
Displacement (C.I.)	1.86
Air coolant	N/A
Bore (mm) x Stroke (mm)	88.00 x 102.00
Compression ratio	18.5 : 1
Speed (RPM)	1500
Pistons speed (m/s)	5.10
Maximum stand-by power at rated RPM (kW)	19.0
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	7.52
Governor type	Mechanical

COOLING SYSTEM

Radiator & Engine capacity (L)	6.80
Max water temperature (°C)	110
Outlet water temperature (°C)	N/A
Fan power (kW)	0.40
Fan air flow w/o restriction (m ³ /s)	0.65
Available restriction on air flow (mm EC)	N/A
Type of coolant	Glycol-Ethylene
Thermostat (°C)	79-93

EMISSIONS

Emission PM (g/kW.h)	N/A
Emission CO (g/kW.h)	N/A
Emission HCNO _x (g/kWh)	N/A
Emission HC (g/kW.h)	N/A

EXHAUST

Exhaust gas temperature (°C)	520
Exhaust gas flow (L/s)	59.00
Max. exhaust back pressure (mm EC)	500

FUEL

Consumption @ 110% load (L/h)	5.50
Consumption @ 100% load (L/h)	4.80
Consumption @ 75% load (L/h)	3.50
Consumption @ 50% load (L/h)	2.40
Maximum fuel pump flow (L/h)	30.00

OIL

Oil capacity (L)	8.70
Min. oil pressure (bar)	1.50
Max. oil pressure (bar)	10.00
Oil consumption 100% load (L/h)	N/A
Carter oil capacity (L)	8.5

HEAT BALANCE

Heat rejection to exhaust (kW)	13
Radiated heat to ambient (kW)	3.50
Heat rejection to coolant (kW)	16.8

AIR INTAKE

Max. intake restriction (mm EC)	150
Intake air flow (L/s)	18.70



K22

ALTERNATOR CHARACTERISTICS

GENERAL DATA

Alternator brand	MECC ALTE
Alternator ref.	ECP 28 M/4
Number of phase	3
Power factor (Cos Phi)	0.8
Altitude (m)	0 to 1000
Overspeed (rpm)	0
Number of pole	4
Excitation system	MAUX-DSR
Insulation class	H
T° class, continuous 40°C	N/A
AVR Type	DSR
Total Harmonic Distortion in no-load DHT (%)	N/A
Wave form : NEMA=TIF	N/A
Wave form : CEI=FHT	N/A
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	N/A
Recovery time (Delta U = 20% transient) (ms)	N/A

OTHER DATA

Continuous Nominal Rating 40°C (kVA)	20.0
Standby Rating 27°C (kVA)	N/A
Efficiencies 4/4 load (%)	88.0
Air flow (m3/s)	0.053
Short circuit ratio (Kcc)	0.620
Direct axis synchro reactance unsaturated (Xd) (%)	180.0
Quadra axis synchro reactance unsaturated (Xq) (%)	78.0
Open circuit time constant (T"do) (ms)	850.00
Direct axis transient reactance saturated (X"d) (%)	16.8
Short circuit transient time constant (T"d) (ms)	44.000
Direct axis subtransient reactance saturated (X""d) (%)	9.6
Subtransient time constant (T""d) (ms)	14.000
Quadra axis subtransient reactance saturated (X""q) (%)	22.00
Zero sequence reactance unsaturated (Xo) (%)	3.30
Negative sequence reactance saturated (X2) (%)	14.40
Armature time constant (Ta) (ms)	12.000
No load excitation current (io) (A)	0.50
Full load excitation current (ic) (A)	1.50
Full load excitation voltage (uc) (V)	0.0
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	0.00
Transient dip (4/4 load) - PF : 0,8 AR (%)	0.00
No load losses (W)	0.00
Heat rejection (W)	2307.00

DIMENSIONS

BASE AND CANOPY SPECIFICATIONS

Commercial reference of the enclosure	M126 DW
Length (mm).	1797
Width (mm).	775
Height (mm).	1391
Dry weight (kg).	800
Tank capacity (L).	93
Acoustic pressure level @1m in dB(A)	71
Sound power level guaranteed (Lwa)	87



K22

CONTROL PANEL

NEXYS, comprehensive and simple

TELYS, ergonomic and user-friendly

The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (sup. to 60 Kva), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

